

ACTIVE 2

Active 2 is an acidic, medium duty, non foaming liquid descaling agent that removes oxides, light rust, heat and mineral scale from most surfaces. Product is used in automatic and CIP systems.
Product pH at a 1 % dilution is between 1.00 - 2.00.

Dilutions

Use at 20 - 200 ml/L (1:50 - 1:5) dilution with water depending on application requirements. Apply at ambient to 70 °C until clean. Rinse surface well. Do not mix with any other chemicals. Use diluted product within 1 day. Always use gloves, goggles and protective clothing when handling and decanting this product.

GHS Identification:

Danger

UN1760 - Corrosive Liquid N.O.S



PPE

Gloves, Goggles, Personal Protective Clothing, Apron, Gumboots



First Aid

SKIN	EYES	IINHALATION	ORAL
Remove/take off immediately all contaminated clothing. Rinse skin with water. Shower	Rinse cautiously with water for several minutes, remove contact lenses if safe and easy to do so, continue rinsing and get medical attention	If INHALED remove person to fresh air and keep comfortable for breathing.	Rinse mouth thoroughly
If skin irritation persists consult a doctor.			Consult a Doctor immediately
			Do not induce vomiting
			Consult a Doctor immediately

Available in

Drums - 5Lt, 25Lt